

Single Package Air Conditioner and Heat Pump

SPAC/SPHP Series

Designed to condition multiple rooms, the Ice Air Air Conditioners and Heat Pump SPAC family are unique air-to-air units that work on an exterior wall, providing concealed, quiet, cost effective, efficient cooling and heating.

With electric heat and outside air options, Ice Air's SPACs have variations which provide the right solution for any new construction or replacement project.

Features:

- Meets new 11.0 EER requirements
- Electronically commutated motors included



SERIES MODEL #	8SPHP12	8SPHP18	8SPHP24	8SPHP30	8SPHP36
COOLING CAPACITY*	11,500	16,800	24,000	27,500	32,500
SENSIBLE CAPACITY	8,630	12,600	18,000	22,500	24,900
EER	13.0	11.0	11.0	11.0	11.0
COOLING WATTS	884	1,527	2,182	2,500	2,955
COOLING AMP	4.3	7.3	10.4	12.0	14.2
HEATING CAPACITY**	11,400	15,200	19,000	24,000	27,500
HEATING COP	3.5	3.3	3.3	3.3	3.3
HEATING WATTS	955	1,350	1,687	2,130	2,441
HEATING AMP	4.6	6.5	8.1	10.2	11.7
ELECTRIC HEAT	3,515.0	5,017.5	5,017.5	5,017.5	5,017.5
VOLTAGE	208	208	208	208	208
INDOOR CFM	400	600	800	1,000	1,200
MAX. ESP (INDOOR)	0.3"	0.3"	0.3"	0.3"	0.3"
MCA (WITHOUT ELECTRIC HEAT)	10.8	13.3	21.1	23.8	29.4
MAX FUSE (WITHOUT ELECTRIC HEAT)	15	20	30	30	40
MCA (WITH ELECTRIC HEAT)	22.5 27.8	28.7 47.4	28.9 47.8	29.5 48.3	33.3 48.3
MAX FUSE (WITH ELECTRIC HEAT)	25 30	30 50	30 50	30 50	40 50
CHASSIS WEIGHT	180	180	225	320	320

SPECIFICATION NOTES:

* = BTUH @ 95 °F. DB/75 °F. WB OUTDOORS; 80 °F. DB/67 °F. DB INDOORS.

** = BTUH @ 47 °F. DB/43 °F. WB OUTDOORS; 70 °F. DB/60 °F. DB INDOORS.