

Packaged Terminal Air Conditioner for Replacement

RSCM/A/B/C Series

ICE AIRs RSCM/A/B/C Series Replacement and Retrofit units are high energy efficiency PTACs. Designed from the ground up for ultra-high efficiency, they incorporate advanced LEEDs features in a durable and user-friendly package.

Features:

- Ultra-high efficiency – EERs to 10.5
- Advanced tangential indoor blower provides balanced air flow
- Whisper quiet sound levels
- Standard programmable digital touchpad controls
- 5/2 or 7 day programming
- Heavy duty, commercial-grade construction throughout
- G90 galvanized steel construction, powder-coated drain and base pans
- Furniture-grade, powder-coated cabinetry



RSCM/A Replaces:

ClimateMaster 702, 703, 704
 Friedrich – 702, 703, 704
 Weil-McClain – 702, 703, 704
 Islandaire – CM
 Retroaire – RC/RH20

RSCM/B and RSCM/C Replaces:

ClimateMaster – 700 AD
 Friedrich – 700 AD
 Weil-McClain – 700 AD
 Islandaire – AD
 Retroaire – RC/RH20

MODEL		5RSCM09	5RSCM13	8RSCM09	8RSCM13	8RSCM18	7RSCM09	7RSCM13	7RSCM19
Cooling	Capacity	9,500	12,750	9,700	13,250	17,300	9,250	12,500	17,000
	EER	10.5	8.2	10.3	8.1	7.7	10.5	10	9.3
Heating Capacity	Hot Water	16,500	16,500	16,500	16,500	16,500	16,500	16,500	19,400
	Steam	18,700	18,700	18,700	18,700	18,700	18,700	18,700	20,000
Electric Heat Max.		1.5KW	1.5KW	1.5KW	3.5/4.3KW	3.5/4.3KW	1.5KW	3.5/4.3KW	3.5/4.3KW
Voltage		115	115	208/230	208/230	208/230	277	277	277
Cooling	Amperage	7.4	10.9	4.2	6.4	9.0	3.0	4.4	6.6
	Watts	905	1,555	942	1,636	2,247	881	1,250	1,828
CFM Air Hi Cool		370	370	370	430	480	370	430	480
Weight Net		113	117	113	124	141	117	124	141
Weight Shipped		129	133	129	138	157	133	139	157