

Packaged Terminal Air Conditioner for Replacement

RSMK Series

Ice Air's RSMK Series Replacement and Retrofit units are high energy efficiency PTACs. Designed from the ground up for ultra-high efficiency, they incorporate advanced LEEDs features in a durable and user-friendly package.

Features:

- Ultra-high efficiency – EERs to 9.1
- Advanced tangential indoor blower provides balanced air flow
- Whisper quiet sound levels
- Standard programmable digital touchpad controls
- 5/2 or 7 day programming
- Heavy duty, commercial-grade construction throughout
- G90 galvanized steel construction, powder-coated drain and base pans
- Furniture-grade, powder-coated cabinetry



Replaces:

Singer – K, EK
Remington – K, EK
McQuay – K, EK, RK
Ice-Cap – RSK/K, RSMK

SERIES MODEL #	5RSMK09	8RSMK13	8RSMK16
Cooling Capacity ¹ (BTU/h)	11,100	12,500	13,500
EER	9.3	8.3	8.1
Heating Capacity - Hot Water ² (BTU/h)	16,500	16,500	19,400
Heating Capacity - Steam ³ (BTU/h)	18,700	18,700	20,000
Electric Heating MAX (kW)	1.5	4.3	4.3
Voltage	115	208/230	208/230
Amperage	10.4	7.2	8.0
Watts	1194	1506	1667
Airflow AC High Speed (CFM)	370	430	430
Airflow AC Low Speed (CFM)	350	370	370

SPECIFICATION NOTES:

1. Cooling mode performance ratings are in compliance with AHRI standard 310/380 and CSA standard 744.
2. BTUH @ 200 °F. E.W.T.; 65 °F. E.A.T. & 2 G.P.M. flow rate.
3. BTUH @ 2 PSIG STEAM & 65 °F. E.A.T.
4. Performance data based on R32 green refrigerant.

IMPORTANT: Additional voltages and alternate electric heat and heat pump options are available. For performance data and other available options please consult factory. Accessories are optional. Deviations from standard accessories may affect performance; louver requires 70% free area per original OEM specification; room enclosures must provide sufficient return air, free flowing supply air and must be properly sealed to prevent air recirculation; any non-standard components or accessories must be reviewed and approved by Ice Air or approved distributor.