

Packaged Terminal Air Conditioner for Replacement

RSF Series

Ice Air's RSF Series Replacement and Retrofit units are high energy efficiency PTACs. Designed from the ground up for ultra-high efficiency, they incorporate advanced LEEDs features in a durable and user-friendly package.

Features:

- Ultra-high efficiency – EERs to 9.5
- Advanced tangential indoor blower provides balanced air flow
- Whisper quiet sound levels
- Standard programmable digital touchpad controls
- 5/2 or 7 day programming
- Heavy duty, commercial-grade construction throughout
- G90 galvanized steel construction, powder-coated drain and base pans
- Furniture-grade, powder-coated cabinetry



Replaces:

Fedders – MaxiZone
 Islandaire – MX
 Retroaire – RC40

SERIES MODEL #	5RSF13	8RSF13	8RSF16
COOLING CAPACITY*	12,100	12,100	14,300
EER	9.5	9.6	9.5
HEATING CAPACITY (HOT WATER)**	15,500	15,500	15,500
HEATING CAPACITY (STEAM)***	18,700	18,700	18,700
ELECTRIC HEATING MAX. (KW)	1.5	4.3	4.3
VOLTAGE	115	208/230	208/230
AMPERAGE	11.1	6.1	7.2
WATTS	1,274	1,260	1,505
CFM AIR HI COOL	350	350	400
CFM AIR LO COOL	280	280	310
CFM OUTSIDE AIR	60	60	60
WEIGHT NET/SHIP	117/133	117/133	121/138

SPECIFICATION NOTES:

- 1: * = BTUH @ 80°F. DB/67 °F. WB INDOORS; 95 °F. DB OUTDOORS.
- 2: ** = BTUH @ 200 °F. E.W.T.; 65 °F. E.A.T. & 2 G.P.M. FLOW RATE.
- 3: *** = BTUH @ 2 PSIG STEAM & 65 °F. E.A.T.

IMPORTANT: Accessories are optional. Deviations from standard accessories may affect performance; louver requires 70% free area per original OEM specification; room enclosures must provide sufficient return air, free flowing supply air and must be properly sealed to prevent air recirculation; any non-standard components or accessories must be reviewed and approved by Ice Air or approved distributor.