

Packaged Terminal Air Conditioner for Replacement

# RSCM/A/B/C Series

Ice Air's RSCM/A/B/C Series Replacement and Retrofit units are high energy efficiency PTACs. Designed from the ground up for ultra-high efficiency, they incorporate advanced LEEDs features in a durable and user-friendly package.

## Features:

- Ultra-high efficiency – EERs to 10.5
- Advanced tangential indoor blower provides balanced air flow
- Whisper quiet sound levels
- Standard programmable digital touchpad controls
- 5/2 or 7 day programming
- Heavy duty, commercial-grade construction throughout
- G90 galvanized steel construction, powder-coated drain and base pans
- Furniture-grade, powder-coated cabinetry



## RSCM/A Replaces:

ClimateMaster 702, 703, 704  
 Friedrich – 702, 703, 704  
 Weil-McClain – 702, 703, 704  
 Islandaire – CM  
 Retroaire – RC/RH20

## RSCM/B and RSCM/C Replaces:

ClimateMaster – 700 AD  
 Friedrich – 700 AD  
 Weil-McClain – 700 AD  
 Islandaire – AD  
 Retroaire – RC/RH20

SERIES MODEL #	5RSCM09	5RSCM13	8RSCM09	8RSCM13	8RSCM18	7RSCM09	7RSCM13	7RSCM18
<b>COOLING CAPACITY*</b>	9,500	12,750	9,700	13,250	17,300	9,250	12,500	17,000
<b>EER</b>	10.5	8.2	10.3	8.1	7.7	10.5	10	9.3
<b>HEATING CAPACITY (HOT WATER)**</b>	16,500	16,500	16,500	16,500	16,500	16,500	16,500	19,400
<b>HEATING CAPACITY (STEAM)***</b>	18,700	18,700	18,700	18,700	18,700	18,700	18,700	20,200
<b>ELECTRIC HEATING MAX. (KW)</b>	1.5	1.5	4.3	4.3	4.3	3.5	3.5	3.5
<b>VOLTAGE</b>	115	115	208/230	208/230	208/230	277	277	277
<b>AMPERAGE</b>	7.9	13.5	4.5	7.9	10.8	3.2	4.5	6.6
<b>WATTS</b>	905	1,555	942	1,636	2,247	881	1,250	1,828
<b>CFM ROOM AIR HIGH</b>	370	370	370	430	480	370	430	480
<b>WEIGHT NET/SHIP</b>	113/129	117/133	113/129	124/138	141/157	117/133	124/139	141/157

## SPECIFICATION NOTES:

1:\* = BTUH @ 80°F. DB/67 °F. WB INDOORS; 95 °F. DB OUTDOORS.

2:\*\* = BTUH @ 200 °F. E.W.T.; 65 °F. E.A.T. & 2 G.P.M. FLOW RATE.

3:\*\*\* = BTUH @ 2 PSIG STEAM & 65 °F. E.A.T.

**IMPORTANT:** Accessories are optional. Deviations from standard accessories may affect performance; louver requires 70% free area per original OEM specification; room enclosures must provide sufficient return air, free flowing supply air and must be properly sealed to prevent air recirculation; any non-standard components or accessories must be reviewed and approved by Ice Air or approved distributor.