

Packaged Terminal Air Conditioner for Replacement

# RSMK Series

Ice Air's RSMK Series Replacement and Retrofit units are high energy efficiency PTACs. Designed from the ground up for ultra-high efficiency, they incorporate advanced LEEDs features in a durable and user-friendly package.

## Features:

- Ultra-high efficiency – EERs to 9.1
- Advanced tangential indoor blower provides balanced air flow
- Whisper quiet sound levels
- Standard programmable digital touchpad controls
- 5/2 or 7 day programming
- Heavy duty, commercial-grade construction throughout
- G90 galvanized steel construction, powder-coated drain and base pans
- Furniture-grade, powder-coated cabinetry



## Replaces:

Singer – K, EK  
 Remington – K, EK  
 McQuay – K, EK, RK  
 Ice-Cap – RSK/K, RSMK

SERIES MODEL #	5RSMK09	5RSMK13	8RSMK13	8RSMK16	7RSMK09	7RSMK13
<b>COOLING CAPACITY*</b>	8,550	11,750	11,500	13,500	8,550	11,750
<b>EER</b>	9.1	8.4	8.5	8.05	9.1	8.4
<b>HEATING CAPACITY (HOT WATER)**</b>	16,500	16,500	16,500	19,400	16,500	16,500
<b>HEATING CAPACITY (STEAM)***</b>	18,700	18,700	18,700	20,000	18,700	18,700
<b>ELECTRIC HEATING MAX. (KW)</b>	1.5	1.5	4.3	4.3	3.5	3.5
<b>VOLTAGE</b>	115	115	208/230	208/230	277	277
<b>AMPERAGE</b>	8.2	12.2	6.5	8.1	3.4	5.0
<b>WATTS</b>	940	1,399	1,353	1,677	940	1,399
<b>CFM ROOM AIR HIGH</b>	370	370	430	430	370	370
<b>CFM ROOM AIR LOW</b>	350	350	370	370	350	350

## SPECIFICATION NOTES:

- 1: \* = BTUH @ 80°F. DB/67 °F. WB INDOORS; 95 °F. DB OUTDOORS.
- 2: \*\*= BTUH @ 200 °F. E.W.T.; 65 °F. E.A.T. & 2 G.P.M. FLOW RATE.
- 3: \*\*\* = BTUH @ 2 PSIG STEAM & 65 °F. E.A.T.

**IMPORTANT:** Accessories are optional. Deviations from standard accessories may affect performance; louver requires 70% free area per original OEM specification; room enclosures must provide sufficient return air, free flowing supply air and must be properly sealed to prevent air recirculation; any non-standard components or accessories must be reviewed and approved by Ice Air or approved distributor.