

Packaged Terminal Air Conditioner for Replacement

RSZ Series

Ice Air's RSZ Series Replacement and Retrofit units are high energy efficiency PTACs. Designed from the ground up for ultra-high efficiency, they incorporate advanced LEEDs features in a durable and user-friendly package.

Features:

- Ultra-high efficiency – EERs to 8.9
- Advanced tangential indoor blower provides balanced air flow
- Whisper quiet sound levels
- Standard programmable digital touchpad controls
- 5/2 or 7 day programming
- Heavy duty, commercial-grade construction throughout
- G90 galvanized steel construction, powder-coated drain and base pans
- Furniture-grade, powder-coated cabinetry



Replaces:

Cool Heat – RM
 Embassy – Weather Twin
 TPI – RaMATIC
 ZoneAire – RM, SC
 Islandaire – RM
 Retroaire – RC/RH20

SERIES MODEL #	5RSZ09	5RSZ13	8RSZ09	8RSZ13	8RSZ18	7RSZ09	7RSZ13
COOLING CAPACITY*	9,400	12,800	9,300	12,750	16,300	9,200	12,800
EER	8.9	8.2	8.95	8.2	7.7	8.95	8.3
HEATING CAPACITY (HOT WATER)**	16,500	16,500	16,500	16,500	19,400	16,500	16,500
HEATING CAPACITY (STEAM)***	18,700	18,700	18,700	18,700	20,200	18,700	18,700
ELECTRIC HEATING MAX. (KW)	1.5	1.5	4.3	4.3	4.3	3.5	3.5
VOLTAGE	115	115	208/230	208/230	208/230	277	277
AMPERAGE	9.2	13.6	5.0	7.5	10.2	3.7	5.6
WATTS	1,056	1,561	1,039	1,555	2,117	1,028	1,542
CFM AIR HIGH	370	370	370	430	430	370	370
CFM AIR LOW	260	260	260	330	330	260	260

SPECIFICATION NOTES:

1:* = BTUH @ 80°F. DB/67 °F. WB INDOORS; 95 °F. DB OUTDOORS.

2:** = BTUH @ 200 °F. E.W.T.; 65 °F. E.A.T. & 2 G.P.M. FLOW RATE.

3:*** = BTUH @ 2 PSIG STEAM & 65 °F. E.A.T.

IMPORTANT: Accessories are optional. Deviations from standard accessories may affect performance; lower requires 70% free area per original OEM specification; room enclosures must provide sufficient return air, free flowing supply air and must be properly sealed to prevent air recirculation; any non-standard components or accessories must be reviewed and approved by Ice Air or approved distributor.